




order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## 2212 EK TN-NSK SFÆRISK KUGLELEJE ÅBENT MED KONISK HUL



Self aligning ball bearing with tapered bore from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality

### Basic dimensions

|                    |        |    |
|--------------------|--------|----|
| Width [B]          | 28.00  | mm |
| Inner diameter [d] | 60.00  | mm |
| Outer diameter [D] | 110.00 | mm |

### Physical properties

|                             |           |     |
|-----------------------------|-----------|-----|
| Load Radial Static [C0r]    | 12 600.00 | n   |
| Load Radial Dynamic [Cr]    | 34 000.00 | n   |
| Weight                      | 1.03      | kg  |
| Load rating static [C0r]    | 12 600.00 | n   |
| Limiting speed oil [rpm]    | 6 300.00  | rpm |
| Load rating dynamic [Cr]    | 34 000.00 | n   |
| Limiting speed grease [rpm] | 5 300.00  | rpm |

## Other data

|                              |           |    |
|------------------------------|-----------|----|
| Ref diam shaft min [da min]  | 68.00     | mm |
| Ref diam groove max [Da max] | 102.00    | mm |
| Cage Type                    | Polyamide |    |
| Radius min [r min]           | 1.50      | mm |
| Bore type                    | Tapered   |    |