



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

22211 EA W33 ZZ C3-SNR SFÆRISK RULLELEJE MED METALTÆTNINGER OG CYLINDRISK HUL

The most common reasons for shortened lifetime are dirt penetrating the bearing or the bearing does not retain the lubricant. The rubber-sealed spherical roller bearings have their limitations in not being able to manage the same speed, not being equally heat resistant, and that they don't keep the ISO width dimensions. KIZEI can withstand the same loads as unsealed spherical roller bearings and because it meets the ISO standard, it has the same dimensions. Temperature range is -40 ° C to + 200 °.

Basic dimensions

| | | |
|--------------------|--------|----|
| Width [B] | 25.00 | mm |
| Inner diameter [d] | 55.00 | mm |
| Outer diameter [D] | 100.00 | mm |

Physical properties

| | | |
|-----------------------------|------------|-----|
| Weight | 0.85 | kg |
| Load rating dynamic [Cr] | 155 000.00 | n |
| Limiting speed oil [rpm] | 5 500.00 | rpm |
| Load rating static [C0r] | 148 000.00 | n |
| Limiting speed grease [rpm] | 4 300.00 | rpm |

Other data

| | |
|-----------|---------------------|
| Bore type | Cylindrical |
| Cage Type | Two Metal Shield ZZ |
| Clearance | C3 |