



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

22213 EA K W33 ZZ C3-SNR SFÆRISK RULLELEJE MED METALTÆTNINGER OG KONISK HUL

The most common reasons for shortened lifetime are dirt penetrating the bearing or the bearing does not retain the lubricant. The rubber-sealed spherical roller bearings have their limitations in not being able to manage the same speed, not being equally heat resistant, and that they don't keep the ISO width dimensions. KIZEI can withstand the same loads as unsealed spherical roller bearings and because it meets the ISO standard, it has the same dimensions. Temperature range is -40 ° C to + 200 °.

Basic dimensions

| | | |
|--------------------|--------|----|
| Width [B] | 31.00 | mm |
| Outer diameter [D] | 120.00 | mm |
| Inner diameter [d] | 65.00 | mm |

Physical properties

| | | |
|---------------------------------------|------------|-----|
| Weight | 1.54 | kg |
| Load rating static [C _{0r}] | 224 000.00 | n |
| Limiting speed grease [rpm] | 3 600.00 | rpm |
| Limiting speed oil [rpm] | 4 700.00 | rpm |
| Load rating dynamic [C _r] | 226 000.00 | n |

Other data

| | |
|-----------|---------------------|
| Clearance | C3 |
| Bore type | Tapered |
| Cage Type | Two Metal Shield ZZ |