



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## 51406-NSK AKSIALKUGLELEJE ENKELTVIRKENDE

High quality single acting thrust ball bearing from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Outer diameter [D] | 70.00 | mm |
| Inner diameter [d] | 30.00 | mm |
| Width [B]          | 28.00 | mm |

### Physical properties

|                                |            |     |
|--------------------------------|------------|-----|
| Limiting speed oil [rpm]       | 3 400.00   | rpm |
| Axial dynamic load rating [Ca] | 73 000.00  | n   |
| Weight                         | 0.52       | kg  |
| Axial static load rating [C0a] | 126 000.00 | n   |
| Axial static load rating [C0a] | 12 800.00  |     |
| Limiting speed grease [rpm]    | 2 200.00   | rpm |
| Axial dynamic load rating [Ca] | 7 450.00   |     |

### Other data

|                              |           |    |
|------------------------------|-----------|----|
| Type                         | Flat Seat |    |
| Radius min [r min]           | 1.00      | mm |
| Diam inner outer ring        | 32.00     | mm |
| Ref rad max [ra max]         | 1.00      | mm |
| Ref diam shaft min [da min]  | 54.00     | mm |
| Diam outer center ring       | 70.00     | mm |
| Ref diam groove max [Da max] | 46.00     | mm |