



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

6004 ZZ NR-NSK SPORKUGLELEJE ENRADET MED METALTÆTNINGER



High quality steel shielded Deep groove ball bearing with locating snap ring on the outer diameter from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality

Basic dimensions

Width [B]	12.00	mm
Inner diameter [d]	20.00	mm
Outer diameter [D]	42.00	mm

Physical properties

Load rating dynamic kgf	955.00
-------------------------	--------

Load rating dynamic [Cr]	9 400.00	n
Limiting speed grease [rpm]	18 000.00	rpm
Load rating static kgf	510.00	
Weight	0.07	kg
Load rating static [C0r]	5 000.00	n

Other data

Dist groove max [a]	2.06	mm
Groove snap ring	With Snap Ring	
Ref diam groove [Dx]	47.00	mm
Radius min [r]	0.60	mm
Seal type	Two Metal Shield ZZ	
Thickness snap ring max [f]	1.12	mm
Diam outer snap ring max [D2]	46.30	mm
Ref rad max [ra]	0.60	mm
Ref diam groove max [Da]	38.00	mm
Factor	13.80	
Rad outer min [rN]	0.50	mm
Ref dist groove [Cy]	2.90	mm
Ref diam shaft max [da]	25.50	mm
Width groove min [b]	1.35	mm
Ref diam shaft min [da]	24.00	mm