



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

6007 Z NR-NSK SPORKUGLELEJE ENRADET MED EN METALTÆTNING

High quality Deep groove ball bearing steel shielded on one side with locating snapping on the outer diameter from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality

Basic dimensions

Width [B]	14.00	mm
Outer diameter [D]	62.00	mm
Inner diameter [d]	35.00	mm

Physical properties

Load rating static [C _{0r}]	10 300.00	n
Load rating dynamic kgf	1 630.00	
Load rating dynamic [C _r]	16 000.00	n
Load rating static kgf	1 050.00	
Weight	0.15	kg
Limiting speed grease [rpm]	11 000.00	rpm

Other data

Ref diam groove [D _x]	68.50	mm
Groove snap ring	With Snap Ring	
Diam groove max [D ₁]	59.61	mm
Ref rad max [r _a]	1.00	mm
Width groove min [b]	1.90	mm
Ref diam shaft min [d _a]	40.00	mm
Ref diam groove max [D _a]	57.00	mm
Radius min [r]	1.00	mm
Diam outer snap ring max [D ₂]	67.70	mm
Seal type	Two Metal Shield ZZ	
Ref diam shaft max [d _a]	41.50	mm

Ref dist groove [Cy]	3.40	mm
Factor	14.80	
Dist groove max [a]	2.08	mm
Thickness snap ring max [f]	1.70	mm
Rad outer min [rN]	0.50	mm