




order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

6202 2RS NR-NSK SPORKUGLELEJE MED GUMMITÆTNINGER OG LÅSERING



High quality Deep groove ball bearing with locating snap ring on the outer diameter and rubber contact seals from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality. The unique & patented NSK DDU rubber seal features market leading technology, keeping contaminants and moisture out of the bearing while retaining the high class lubricant inside

Basic dimensions

Inner diameter [d]	15.00	mm
Width [B]	11.00	mm
Outer diameter [D]	35.00	mm

Physical properties

Load rating static [C _{0r}]	3 750.00	n
Weight	0.05	kg
Load rating static kgf	380.00	
Limiting speed grease [rpm]	14 000.00	rpm
Load rating dynamic kgf	780.00	
Load rating dynamic [C _r]	7 650.00	n

Other data

Ref diam groove max [Da]	31.00	mm
Thickness snap ring max [f]	1.12	mm
Dist groove max [a]	2.06	mm
Groove snap ring	With Snap Ring	
Rad outer min [rN]	0.50	mm
Factor	13.20	
Width groove min [b]	1.35	mm
Radius min [r]	0.60	mm
Ref diam shaft min [da]	19.00	mm
Ref diam groove [Dx]	40.50	mm
Ref diam shaft max [da]	20.50	mm
Diam outer snap ring max [D2]	39.70	mm
Ref dist groove [Cy]	2.90	mm
Ref rad max [ra]	0.60	mm
Seal type	Contact Sealed 2RS	