




order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

6300 2RS C3-NSK SPORKUGLELEJE ENRADET MED GUMMITÆTNINGER



High quality Deep groove ball bearing with rubber contact seals from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality. The unique & patented NSK DDU rubber seal features market leading technology, keeping contaminants and moisture out of the bearing while retaining the high class lubricant inside

Basic dimensions

Outer diameter [D]	35.00	mm
Width [B]	11.00	mm
Inner diameter [d]	10.00	mm

Physical properties

Load rating dynamic [Cr]	8 100.00	n
--------------------------	----------	---

Load rating static [C0r]	3 450.00	n
Load rating dynamic kgf	825.00	
Load rating static kgf	350.00	
Limiting speed grease [rpm]	17 000.00	rpm
Weight	0.05	kg

Other data

Factor	11.20	
Seal type	Contact Sealed DD/DDU	
Ref diam groove max [Da max]	31.00	mm
Radius min [r min]	0.60	mm
Ref rad max [ra max]	0.60	mm
Ref diam shaft max	16.50	mm
Clearance	C3	
Ref diam shaft min [da min]	14.00	mm

Other

factor	11.20	mm
factor	11.20	