



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## 6317 ZZ-NSK SPORKUGLELEJE ENRADET MED METALTÆTNINGER



High quality steel shielded Deep groove ball bearing from the world leader NSK, the worlds largest ball bearing manufacturer offering unparalleled quality

### Basic dimensions

|                    |        |    |
|--------------------|--------|----|
| Width [B]          | 41.00  | mm |
| Inner diameter [d] | 85.00  | mm |
| Outer diameter [D] | 180.00 | mm |

### Physical properties

|                          |            |   |
|--------------------------|------------|---|
| Load rating dynamic kgf  | 13 500.00  |   |
| Load rating dynamic [Cr] | 133 000.00 | n |

|                             |           |     |
|-----------------------------|-----------|-----|
| Limiting speed grease [rpm] | 3 800.00  | rpm |
| Weight                      | 4.28      | kg  |
| Load rating static [C0r]    | 97 000.00 | n   |

## Other data

|                          |                     |    |
|--------------------------|---------------------|----|
| Radius min [r]           | 3.00                | mm |
| Seal type                | Two Metal Shield ZZ |    |
| Ref rad max [ra]         | 2.50                | mm |
| Ref diam groove max [Da] | 167.00              | mm |
| Factor                   | 13.30               |    |
| Ref diam shaft max [da]  | 110.50              | mm |
| Ref diam shaft min [da]  | 98.00               | mm |