



© Nomo Group

order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## 7908 A5 TR SUL P3-NSK VINKELKONTAKTKUGLELEJE SUPERPRÆCISION

High quality Super precision Angular contact ball bearing, from the worlds leader NSK, the worlds largest ball manufacturer, offering unparalleled quality

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Width [B]          | 12.00 | mm |
| Outer diameter [D] | 62.00 | mm |
| Inner diameter [d] | 40.00 | mm |

### Physical properties

|                             |           |     |
|-----------------------------|-----------|-----|
| Load rating dynamic [Cr]    | 14 300.00 | n   |
| Contact angle               | 25.00     |     |
| Load rating static [C0r]    | 11 200.00 | n   |
| Pemissible axial load       | 8 900.00  | n   |
| Limiting speed oil [rpm]    | 29 500.00 | rpm |
| Limiting speed grease [rpm] | 19 700.00 | rpm |

### Other data

|                       |          |    |
|-----------------------|----------|----|
| Preload               | 0.00     |    |
| Precision class       | 0.00     |    |
| Radius min [r1 min]   | 0.30     | mm |
| Radius min [r]        | 0.60     | mm |
| Cage Type             | Phenolic |    |
| Effective load center | 17.90    | mm |
| Cage guiding          | 0.00     |    |