



© Nomo Group

order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## GE 30 C-LS RADIAL LEDLEJE HÅRDKROM/PTFE

High quality Radial spherical plain bearing Steel/PTFE, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Width [B]          | 22.00 | mm |
| Inner diameter [d] | 30.00 | mm |
| Outer diameter [D] | 47.00 | mm |

### Physical properties

|                          |            |    |
|--------------------------|------------|----|
| Load rating dynamic [Cr] | 65 000.00  | n  |
| Load rating static [C0r] | 166 000.00 | n  |
| Misalignment [°]         | 6.00       |    |
| Weight                   | 0.15       | kg |

### Other data

|                            |       |    |
|----------------------------|-------|----|
| Sliding contact surfaces   | 0.00  |    |
| Radius min [r2 min]        | 0.60  | mm |
| Radius min [r1 min]        | 0.60  | mm |
| Inner ring outer race [dk] | 40.70 | mm |
| Seal type                  | Open  |    |
| Outer ring width [C]       | 18.00 | mm |