



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## GE 40 ES 2GS DF-LS RADIAL LEDLEJE STÅL/STÅL MED GUMMITÆTNINGER

High quality Radial spherical plain bearing Steel/Steel sealed, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Inner diameter [d] | 40.00 | mm |
| Outer diameter [D] | 62.00 | mm |
| Width [B]          | 28.00 | mm |

### Physical properties

|                          |            |    |
|--------------------------|------------|----|
| Load rating dynamic [Cr] | 99 000.00  | n  |
| Weight                   | 0.32       | kg |
| Misalignment [°]         | 7.00       |    |
| Load rating static [C0r] | 495 000.00 | n  |

### Other data

|                            |                    |    |
|----------------------------|--------------------|----|
| Radius min [r2 min]        | 1.00               | mm |
| Outer ring width [C]       | 22.00              | mm |
| Sliding contact surfaces   | 0.00               |    |
| Radius min [r1 min]        | 0.60               | mm |
| Inner ring outer race [dk] | 53.00              | mm |
| Seal type                  | Contact Sealed 2GS |    |