



© Nomo Group

order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## GEEM 35 ES 2RS-LS RADIAL LEDLEJE STÅL/STÅL MED GUMMITÆTNINGER

High quality Radial spherical plain bearing Steel/Steel sealed, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Inner diameter [d] | 35.00 | mm |
| Width [B]          | 35.00 | mm |
| Outer diameter [D] | 55.00 | mm |

### Physical properties

|                          |            |    |
|--------------------------|------------|----|
| Load rating dynamic [Cr] | 79 000.00  | n  |
| Weight                   | 0.25       | kg |
| Load rating static [C0r] | 399 000.00 | n  |
| Misalignment [α]         | 4.00       |    |

### Other data

|                                    |                    |    |
|------------------------------------|--------------------|----|
| Inner ring outer diameter [d1 max] | 40.00              | mm |
| Outer ring width [C]               | 20.00              | mm |
| Seal type                          | Contact Sealed 2RS |    |
| Radius min [r1 min]                | 0.60               | mm |
| Inner ring outer race [dk]         | 47.00              | mm |
| Radius min [r2 min]                | 1.00               | mm |
| Sliding contact surfaces           | 0.00               |    |