



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## GX 35 T-LS AKSIAL LEDLEJE STÅL/PTFE

High quality Thrust spherical plain bearing Steel/PTFE, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Inner diameter [d] | 35.00 | mm |
| Width [B]          | 22.00 | mm |
| Outer diameter [D] | 90.00 | mm |

### Physical properties

|                          |              |    |
|--------------------------|--------------|----|
| Misalignment [°]         | 5.00         |    |
| Load rating dynamic [Ca] | 490 000.00   | n  |
| Load rating static [C0a] | 1 200 000.00 | n  |
| Weight                   | 0.97         | kg |

### Other data

|                            |       |    |
|----------------------------|-------|----|
| Hight [H]                  | 28.00 | mm |
| Sliding contact surfaces   | 0.00  |    |
| D1 min                     | 50.50 | mm |
| Inner ring outer race [dk] | 98.00 | mm |
| Radius min [rs]            | 1.00  | mm |
| S                          | 22.00 | mm |
| Seal type                  | Open  |    |
| Outer ring width [C]       | 20.70 | mm |
| d1 max                     | 84.00 | mm |