




© Nomo Group

order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## NJ 2211 ET C3-NSK CYLINDRISK RULLELEJE ENRADET MED POLYAMIDHOLDER



High quality cylindrical roller bearing with polyamide resin cage cage from the leading manufacturer NSK

### Basic dimensions

|                    |        |    |
|--------------------|--------|----|
| Inner diameter [d] | 55.00  | mm |
| Width [B]          | 25.00  | mm |
| Outer diameter [D] | 100.00 | mm |
| Outer diameter [D] | 100.00 | mm |

### Physical properties

|                             |            |     |
|-----------------------------|------------|-----|
| Load rating static [C0r]    | 122 000.00 | n   |
| Limiting speed oil [rpm]    | 7 100.00   | rpm |
| Limiting speed grease [rpm] | 5 600.00   | rpm |
| Load rating dynamic [Cr]    | 101 000.00 | n   |

## Other data

|                          |           |    |
|--------------------------|-----------|----|
| Da max                   | 92.00     | mm |
| db min                   | 61.50     | mm |
| Clearance                | C3        |    |
| Design                   | NJ        |    |
| Cage Type                | Polyamide |    |
| da                       | 64.00     | mm |
| Cage Material            | P         |    |
| Inner ring race diameter | 66.00     | mm |
| Radius min [r min]       | 1.50      | mm |
| Weight                   | 0.78      | kg |
| ra max                   | 1.50      | mm |
| Radius 1 min [r1 min]    | 1.10      | mm |