



## NU 2319 W-NSK CYLINDRISK RULLELEJE ENRADET MED STÅLHOLDER



High quality cylindrical roller bearing with pressed steel cage cage from the leading manufacturer NSK

### Basic dimensions

|                    |        |    |
|--------------------|--------|----|
| Inner diameter [d] | 95.00  | mm |
| Width [B]          | 67.00  | mm |
| Outer diameter [D] | 200.00 | mm |
| Outer diameter [D] | 200.00 | mm |

### Physical properties

|                             |            |     |
|-----------------------------|------------|-----|
| Load rating static [C0r]    | 585 000.00 | n   |
| Limiting speed oil [rpm]    | 3 400.00   | rpm |
| Limiting speed grease [rpm] | 2 600.00   | rpm |
| Load rating dynamic [Cr]    | 460 000.00 | n   |

## Other data

|                          |        |    |
|--------------------------|--------|----|
| Da max                   | 187.00 | mm |
| db min                   | 108.00 | mm |
| Design                   | NU     |    |
| Cage Type                | Steel  |    |
| da                       | 118.00 | mm |
| Cage Material            | S      |    |
| Inner ring race diameter | 121.50 | mm |
| rb max                   | 2.50   | mm |
| Radius min [r min]       | 3.00   | mm |
| Weight                   | 9.21   | kg |
| ra max                   | 2.50   | mm |
| Radius 1 min [r1 min]    | 3.00   | mm |