





## NUP 2210 ET-NSK CYLINDRISK RULLELEJE ENRADET MED POLYAMIDHOLDER



High quality cylindrical roller bearing with polyamide resin cage cage from the leading manufacturer NSK

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Inner diameter [d] | 50.00 | mm |
| Width [B]          | 23.00 | mm |
| Outer diameter [D] | 90.00 | mm |
| Outer diameter [D] | 90.00 | mm |

### Physical properties

|                             |           |     |
|-----------------------------|-----------|-----|
| Load rating static [C0r]    | 97 000.00 | n   |
| Limiting speed oil [rpm]    | 8 000.00  | rpm |
| Limiting speed grease [rpm] | 6 300.00  | rpm |
| Load rating dynamic [Cr]    | 83 500.00 | n   |

## Other data

|                          |           |    |
|--------------------------|-----------|----|
| Da max                   | 83.50     | mm |
| db min                   | 56.50     | mm |
| Design                   | NUP       |    |
| Cage Type                | Polyamide |    |
| da                       | 57.00     | mm |
| Cage Material            | P         |    |
| Inner ring race diameter | 59.50     | mm |
| rb max                   | 1.00      | mm |
| Radius min [r min]       | 1.50      | mm |
| Weight                   | 0.56      | kg |
| ra max                   | 1.00      | mm |
| Radius 1 min [r1 min]    | 1.50      | mm |