



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## SAL 12 E-LS LEDSTANGSHOVED STÅL/STÅL MED UDV. VENSTREGEVIND

High quality Rod end Steel/Steel Left Outer thread, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Width [B]          | 10.00 | mm |
| Inner diameter [d] | 12.00 | mm |

### Physical properties

|                                       |           |    |
|---------------------------------------|-----------|----|
| Weight                                | 0.07      | kg |
| Load rating static [C <sub>0r</sub> ] | 23 000.00 | n  |
| Load rating dynamic [C <sub>r</sub> ] | 10 000.00 | n  |

### Other data

|                                 |              |    |
|---------------------------------|--------------|----|
| d <sub>2</sub>                  | 34.00        | mm |
| l <sub>2</sub>                  | 71.00        | mm |
| Seal type                       | Open         |    |
| Thread                          | 0.00         |    |
| C <sub>1</sub> max              | 8.50         | mm |
| Sliding contact surfaces        | 0.00         |    |
| h                               | 54.00        | mm |
| l <sub>7</sub>                  | 18.00        | mm |
| Radius min [r <sub>s</sub> min] | 0.30         | mm |
| dk                              | 18.00        | mm |
| l <sub>1</sub> min              | 28.00        | mm |
| Thread size [G]                 | 0.00         |    |
| Type                            | Outer thread |    |
| Misalignment [°]                | 10.00        |    |