



order@nomo.se | +45 44 20 86 00 | <https://nomo.dk>

## SIL 10 E-LS LEDSTANGSHOVED STÅL/STÅL MED INDV. VENSTREGEVIND

High quality Rod end Steel/Steel Left Inner thread, from LS, providing excellent products and service, top 100 enterprises of China Machinery industry, is the largest supplier and exporter of spherical plain bearings in China.

### Basic dimensions

|                    |       |    |
|--------------------|-------|----|
| Inner diameter [d] | 10.00 | mm |
| Width [B]          | 9.00  | mm |

### Physical properties

|                          |           |    |
|--------------------------|-----------|----|
| Weight                   | 0.07      | kg |
| Load rating dynamic [Cr] | 8 100.00  | n  |
| Load rating static [C0r] | 17 600.00 | n  |

### Other data

|                          |              |    |
|--------------------------|--------------|----|
| Misalignment [°]         | 12.00        |    |
| Sliding contact surfaces | 0.00         |    |
| W                        | 16.00        | mm |
| l3 min                   | 20.00        | mm |
| d4                       | 19.00        | mm |
| Seal type                | Open         |    |
| dk                       | 16.00        | mm |
| l4                       | 57.50        | mm |
| Radius min [rs min]      | 0.30         | mm |
| Type                     | Inner thread |    |
| h1                       | 43.00        | mm |
| d3                       | 16.00        | mm |
| l5                       | 6.50         | mm |
| d2                       | 29.00        | mm |
| Thread size [G]          | 0.00         |    |

|        |       |    |
|--------|-------|----|
| I7     | 15.00 | mm |
| C1 max | 7.50  | mm |
| Thread | 0.00  |    |